

HIGH TEMPERATURE ADHESIVE TAPE



Specifications:

1. Polyimide base film coating with high temperature Silicone adhesive;
2. High temperature and corrosion resistance;
3. Strong adhesion;
4. Soft and proper and no residue after peeling off.
5. For electronic manufacturing industry.

Backing	Polyimide	Polyimide	Polyimide	Polyimide	Polyimide	Polyimide	Polyimide	Polyimide	Polyimide
Adhesive type	Silicone	Silicone	Silicone	Silicone	Silicone	Silicone	Silicone	Silicone	Silicone
Backing Thickness(mm)	0.02	0.025	0.025	0.025	0.05	0.05	0.075	0.1	0.125
Adhesive thickness(mm)	0.025	0.025	0.035	0.045	0.03	0.05	0.045	0.05	0.055
Total Thickness(mm)	0.045	0.05	0.06	0.07	0.08	0.1	0.12	0.15	0.18
Color	amber	amber	amber	amber	amber	amber	amber	amber	amber
Adhesive strength(kg/25mm)	0.5~0.6	0.6~0.7	0.6~0.7	0.6~0.7	0.6~0.7	0.6~0.7	0.6~0.7	0.6~0.7	0.6~0.7
Elongation (%)	14	14	14	14	26	26	40	68	85
Corrosion resistance	1	1	1	1	1	1	1	1	1
Heat resistance(°C)	258°C	258°C	258°C	258°C	258°C	258°C	258°C	258°C	258°C
Length(m)	50	50	33	50	33	33	33	33	33